



Synthetic Fork Oil

Applications

Castrol Fork Oil Synthetic 10W is a fully synthetic suspension fluid designed to provide the ultimate damping performance in all on and off road suspensions.

Castrol Fork Oil Synthetic is suitable for suspension damper units for high performance on and off road motorcycles, (including motocross) and road machines from Yamaha, Honda, Kawasaki and European makes.

Features / Benefits

Castrol Fork Oil Synthetic provides the following benefits:-

- ultimate damping performance over a wide range of temperatures
- rapid air release for anti-fade performance
- wear protection for long suspension component life
- protection against corrosion of all the internal parts

Specifications / Performance

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods

Units

Value:

SAE 10W

TEST	DATA
Density @ 20°C, Kg/m ³	0.830
Viscosity at 100°C, mm ² /s	7.5
Viscosity at 40°C, mm ² /s	42
VI	150
Pour Point °C	-57
Flash Point °C	220

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk
Telephone: 01793 512712
Automotive Technical Helpline: 01793 452222
Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland www.castrol.com/ie
Automotive Technical Helpline: 1800 509 353
Orders/Enquiries: 01 866 5100
